

PolyAdd^M 2893

APPLICATION:

PolyAddTM 2893 anti-foam additive is primarily used in internal combustion engine oil, gear oil, hydraulic oil as defoamer. It also can be applied for demoulding, waterproof, anti-mold and insulation in the rubber, plastics and casting industry. It is colorless transparent thick liquid. It has high antifoaming effect, and good chemical stability.

RECOMMENDED DOSAGE:

5.0 – 20.0 mg/kg

TYPICAL CHARACTERISTICS:

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Density	Kg/m ³ @ 25 °C	D4052	900-1100
Flash Point (open cup)	°C	D92	≥300
Pour Point	°C	D97	≤-50
TAN	Mg KOH/g	D664	≤0.01

PACKAGING:

PolyAddTM 2893 can be packed in 200 Ltr drums (net weight: 200kg/drum).

STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 50 deg C.

HANDLING:

Please refer to SH/T0164, for transportation, storage and oil blending. Maximum temperature for handling is 60 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at sales@myshamrockgroup.com