

PolyAdd^M 2920

APPLICATION:

PolyAddTM 2920 is recommended to be combined with other performance chemicals to provide dispersancy and acid neutralization in engine oils.

RECOMMENDED DOSAGE:

5 – 20 Wt%

TYPICAL CHARACTERISTICS:

CHEMICAL PROPERTY	UNIT	METHOD	VALUE
Nitrogen	Wt%	D4927	2.2

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Specific Gravity	@ 15.6 °C	D4052	0.905
Density	lb/gal @ 60 °F	D4052	7.54
Viscosity	cSt @ 100 °C	D445	88
TBN	Mg KOH/gm	D2896	55
Color	-	D1500	6

PACKAGING:

PolyAddTM 2920 can be packed in 200 Ltr drums or bulk.

STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 32 deg C.

HANDLING:

Maximum temperature for handling is 80 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at sales@myshamrockgroup.com