

# PolyAdd<sup>M</sup> 2970

## APPLICATION:

PolyAdd<sup>TM</sup> 2970 is a neutral calcium-based detergent used in gasoline and diesel engine oils to control piston deposits in the high-temperature ring zone. It is also an effective corrosion inhibitor in greases. It is especially well-suited in protecting against salt spray corrosion.

## RECOMMENDED DOSAGE:

0.5 – 2.5 Wt%

## TYPICAL CHARACTERISTICS:

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Molecular Weight	-	D3712	980
Specific Gravity	@ 15.6 °C	D129	0.99
Active Sulfonate	%	D3673	60
Water	%	D95	0.5
TBN	Mg KOH/g	D2896	10
Viscosity	cSt @ 100 °C	D445	212

## PACKAGING:

PolyAdd<sup>TM</sup> 2970 can be packed in 200 Ltr drums or bulk.

## STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 32 deg C.

## HANDLING:

Maximum temperature for handling is 80 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

## ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at [sales@myshamrockgroup.com](mailto:sales@myshamrockgroup.com)