

PolyLube™ 0912

APPLICATION:

PolyLube™ 0912 is a multipurpose automatic transmission fluid (ATF) additive package designed to meet the performance of requirements of pre-2006 transmissions such as: General Motors – DEXRON® III, Ford – MERCON®, Allison C-4, and Caterpillar TO-2. The product also provides superior thermal and oxidative stability, corrosion protection, wear protection, sludge prevention performance, anti-shudder durability, optimized frictional properties and sludge prevention performance when blended with suitable base stocks.

RECOMMENDED DOSAGE:

PERFORMANCE	MASS %	VI of Finished Oil
Pre-2006 ATF Performance	11.97	179
DEXRON®	8.45	161

TYPICAL CHARACTERISTICS:

CHEMICAL PROPERTY	UNIT	METHOD	VALUE
Boron	Wt%	D4927	0.05
Phosphorus	Wt%	D4951	0.11
Sulfur	Wt%	D4927	0.88

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Density	Lb/gal @ 60° F	D4052	7.55
Specific Gravity	@ 15.6°C	D4052	0.906
Kinematic Viscosity	cSt @ 100°C	D445	230
Appearance	-	Visual	Hazy

PACKAGING:

PolyLube™ 0912 can be packed in 200 Ltr drums or ISO Tanks.

STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 32 deg C.

HANDLING:

Maximum temperature for handling is 80 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at sales@myshamrockgroup.com