

# PolyLube™ 6901

## APPLICATION:

PolyLube™ 6901 contains ashless dispersant and metallic detergents. It provides excellent control of deposits, rust oxidation, bearing corrosion, and wear in Marine engine lubricants formulated with the appropriate base oil.

## RECOMMENDED DOSAGE:

20 Wt%

## TYPICAL CHARACTERISTICS:

CHEMICAL PROPERTY	UNIT	METHOD	VALUE
Zinc	Wt%	D4927	0.0
Sulfur	Wt%	D4927	2.29
Nitrogen	Wt%	D5762	0.11
Calcium	Wt%	D4927	11.43
Phosphorus	Wt%	D4927	0.0

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Density	lb/gal @ 60° F	D4052	9.39
Specific Gravity	@ 15.6° C	D4052	1.12
Viscosity	cSt @ 100 °C	D445	125
Viscosity Index		D2270	156
TBN	Mg KOH/g	D2896	309
Flash	COC °C	D92	180 min
Pour point	°C	D97	-10

## PACKAGING:

PolyLube™ 6901 can be packed in 200 Ltr drums or bulk.

## STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 32 deg C.

## HANDLING:

Maximum temperature for handling is 80 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

## ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at [sales@myshamrockgroup.com](mailto:sales@myshamrockgroup.com)