

PolyLube™ 7802

APPLICATION:

PolyLube™ 7802 is composed of high-quality detergent and dispersant etc. It has good detergency ability, excellent lubricating performance, low-ash and strong exhaust smoke capability. This product can be used in blending 2-stroke air-cooled motorcycle oil .

RECOMMENDED DOSAGE:

API GRADE	JASO LEVEL	MASS %
TA	FA	2.0
TB	FB	3.5
TC	FC	4.5

TYPICAL CHARACTERISTICS:

CHEMICAL PROPERTY	UNIT	METHOD	VALUE
Calcium	Wt%	D4951	≥1.1
Nitrogen	Wt%	D3228	≥0.6

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Density	Kg/m ³ @ 20° C	D4052	Report
Kinematic Viscosity	cSt @ 100°C	D445	Report
Flash Point (open cup)	°C	D92	≥165
TBN	Mg KOH/g	D2896	≥35

PACKAGING:

PolyLube™ 7802 can be packed in 200 Ltr drums (net weight: 170 kg/drum).

STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 50 deg C.

HANDLING:

Maximum temperature for handling is 60 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at sales@myshamrockgroup.com