

PolyLube™ 8987

APPLICATION:

PolyLube™ 8987 contains ashless dispersant, alkyl zinc dithiophosphate and metallic detergents. It provides excellent control of deposits, rust oxidation, bearing corrosion, wear and oil consumption in highly supercharged diesel engines operated in severe service.

RECOMMENDED DOSAGE:

CI-4/SL, CH-4 12.9 Wt %

TYPICAL CHARACTERISTICS:

CHEMICAL PROPERTY	UNIT	METHOD	VALUE
Zinc	Wt%	D4927	1.00
Phosphorus	Wt%	D4927	0.87
Sulfur	Wt%	D4927	2.16
Calcium	Wt%	D4927	2.52
Nitrogen	Wt%	D5762	0.65

PHYSICAL PROPERTY	UNIT	METHOD	VALUE
Density	lb/gal @ 60° F	D4052	7.87
Flash	COC° C	D92	>182
Specific Gravity	@ 15.6° C	D4052	0.95
Viscosity	cSt @ 100°C	D445	40.80
TBN	Mg KOH/g	D2896	80.00

PACKAGING:

PolyLube™ 8987 can be packed in 200 Ltr drums or bulk.

STORAGE:

This product is temperature sensitive. It is strongly recommended that for long term storage the temperature should not exceed 32 deg C.

HANDLING:

Maximum temperature for handling is 80 deg C. Typical precautions for handling concentrated chemicals and blending additives into base oils and solvents should be observed.

ADDITIONAL INFORMATION:

For additional information regarding product, its performance data, availability and MSDS, please contact our Sales Department at sales@myshamrockgroup.com